

Available Models

Model	Recording Speed(Maximum)					
	NTSC			PAL		
Resolution	D1	Half-D1	CIF	D1	Half-D1	CIF
SDVR-4300:4 Channels	30Fps	-	120Fps	25Fps	-	100Fps
SDVR-8300:8 Channels	30Fps	60fps	120Fps	25Fps	50Fps	100Fps
SDVR-16300:16 Channels	30Fps	60fps	120Fps	25Fps	50Fps	100Fps

Specifications

ITEM		4CH	8CH	16CH	
Video	Input	Composite	4CH,Composite 1.0Vp-p, 75 ohm	8CH,Composite 1.0Vp-p, 75 ohm	16CH,Composite 1.0Vp-p, 75 ohm
		Signal Format	NTSC/PAL(Auto Detection)		
		Video Loss	Yes		
	Output	Main Monitor	1CH BNC, 1CH VGA: Selectable		
		Output Level	Composite 1.0Vp-p+_0.2, 75 ohm		
		Signal Format	NTSC/PAL&VGA		
Alarm	Sensor Input	4(NC/NO Selectable)			
	Alarm Output	1			
Recording	Compression	MPEG-4			
	Muiti-Operation	Tricplex(Playback/Record/Network)			
	Frame Rate	Full-D1	704x480(NTSC) / 704x576(PAL)		
		Half-D1	-	704 x 240(NTSC) / 704 x 288(PAL	704 x 240(NTSC) / 704 x 288(PAL
		CIF	352x240(NTSC)/352x288(PAL)		
	Recording quality grade	Low/Standard/High	Low/Standard/High/Super/Ultra		
	Recording Mode	Continuous/Schedule/Motion/Sensor/Manual			
	Motion Detection	Motion Detection Setup by Grid			
Pre & Post Recording	Yes				

Display	Frame Rate	NTSC: 30Fps /PAL: 25 Fps		
Playback	Multi-Decording	1 & 4 split screen	1 & 4, 8 split screen	1 & 4, 8,16split screen
	Search Mode	Event, Time Line, Archive, Log		
Storage	Internal HDD	interface Type	EIDE/ATA 133	SATA
		Max. Capacity of 1 HDD	750GB	
		Max. HDD Number	1	
	File System		NaFS-Designed to prevent dataloss or corruption in the event of apower failure	
	Backup	USB Flash Drive	JPEG & AVI / Exclusive Video Format	
		Network	Video & Still Image	
User I/F	Menu Display	Text UI		
	Input Method	Remote Controller		
Network	Dynamic IP & DDNS	Yes		
	Network Interface	10/100 Base-T Ethernet (RJ-45)		
	Functions	Live, Search, Backup		
	Network Access Type	Network Client Software, Web Viewer, and Multi-site monitoring Software.		
Additional Function	DLS(Day Light Saving)	Yes		
	S/W Upgrade	USB Flash drive		
General	Power Source	DC +12V adapter		
	Unit Weight(Gross Weight)	1.5Kgs(3Kgs) /3.3Lbs(6.6Lbs)		
	Unit Dimension(W x H x D)	340 x 262 x 63 mm /13.4 x 10.3 x2.5inches		

*Specifications are Subject to change without notice.